

**Certifications Standards**

ASME A112.18.1 / CSA B125.1



C

Robinet de bain 2 morceaux avec douchette**Caractéristiques**

- Bec de bain : 39,4 l/min (10.4 gpm) - 60 psi
- Inverseur de type bouton poussoir intégré au bec de bain
- Robinet à double paroi limitant la conduction de la chaleur
- Douchette : Max : 6,6 l/min (1.75 gpm) - 80 psi
- Douchette en laiton ne conduisant pas la chaleur
- Douchette facile à nettoyer

Finis disponibles

CC : Chrome
 KK : Noir mat
 LL : Laiton satiné
 MM : Or ambré
 BB : Blanc
 NN : Nickel brossé
 YY : Nickel poli
 VV : Cuivre satiné
 TT : Bronze vénitien
 GG : Or

FR

2-piece tub filler with hand shower**Features**

- Bath spout: 10.4 gpm (39.4 l/min) - 60 psi
- Tub spout with integrated push-button diverter
- Double-walled faucet limiting heat conduction
- Hand shower: max: 1.75 gpm (6.6 l/min) - 80 psi
- Non-conductive brass hand shower
- Easy-to-clean hand shower

Available finishes

CC: Chrome
 KK: Matte black
 LL: Satin brass
 MM: Warm gold
 BB: White
 NN: Brushed nickel
 YY: Polished nickel
 VV: Satin copper
 TT: Venitian bronze
 GG: Gold

EN

