

B46-1035-00L-xx

PROFILE B46

BARILCertifications Standards

ASME A112.18.1 / CSA B125.1 & NSF / ANSI 61

**Robinet de lavabo monotrou intermédiaire, renvoi non inclus**Caractéristiques

- Max : 4,5 l/min (1.2 gpm) - 60 psi** †
- Aérateur orientable en silicone facile à nettoyer
- Pour lavabo semi-encastré à haut rebord
- Manette latérale
- Commandez votre renvoi de lavabo
- Compatible avec Capteur sans contact ELE-2001-01-xx

Options d'économie d'eau :

- B46-1035-00L-xx-050 : 0.5 gpm / 1,9 L/min†
 B46-1035-00L-xx-100 : 1.0 gpm / 3,7 L/min

Finis disponibles

- CC : Chrome
 KK : Noir mat
 LL : Laiton satiné
 MM : Or ambré
 BB : Blanc
 NN : Nickel brossé
 YY : Nickel poli
 VV : Cuivre satiné
 TT : Bronze vénitien
 GG : Or

FR

Medium single-hole lavatory faucet, drain not includedFeatures

- Max: 1.2 gpm (4,5 l/min) - 60 psi** †
- Easy-to-clean adjustable silicone aerator
- For semi-recessed sink with high rim
- Side handle
- Order your lavatory drain
- Compatible with Touchless Sensor ELE-2001-01-xx

Water saving options:

- B46-1035-00L-xx-050 : 0.5 gpm / 1,9 L/min†
 B46-1035-00L-xx-100 : 1.0 gpm / 3,7 L/min

Available finishes

- CC: Chrome
 KK: Matte black
 LL: Satin brass
 MM: Warm gold
 BB: White
 NN: Brushed nickel
 YY: Polished nickel
 VV: Satin copper
 TT: Venitian bronze
 GG: Gold

EN

