



Certifications Standards

ASME A112.18.1 / CSA B125.1

CEC



Robinet de bain 2 morceaux avec douchette

Caractéristiques

- Bec de bain : 30,4 l/min (8 gpm) - 60 psi
- Inverseur de type bouton poussoir intégré au bec de bain
- Douchette : max : 6,6 l/min (1.75 gpm) - 80 psi
- Douchette en laiton ne conduisant pas la chaleur
- Douchette facile à nettoyer

Finis disponibles

- CC : Chrome
- CK : Chrome noir mat
- KK : Noir mat
- LL : Laiton satiné
- MM : Or ambré
- BB : Blanc
- NN : Nickel brossé
- YY : Nickel poli
- VV : Cuivre satiné
- TT : Bronze vénitien
- GG : Or

FR

2-piece tub filler with hand shower

Features

- Bath spout: 8 gpm (30,4 l/min) - 60 psi
- Tub spout with integrated push-button diverter
- Hand shower: max: 1.75 gpm (6,6 l/min) - 80 psi
- Non-conductive brass hand shower
- Easy-to-clean hand shower

Available finishes

- CC: Chrome
- CK: Chrome matte black
- KK: Matte black
- LL: Satin brass
- MM: Warm gold
- BB: White
- NN: Brushed nickel
- YY: Polished nickel
- VV: Satin copper
- TT: Venitian bronze
- GG: Gold

EN

