

B66-1005-1PL-xx

ZIP B66

BARIL**Certifications Standards**

ASME A112.18.1 / CSA B125.1 & NSF / ANSI 61

**Robinet de lavabo monotrou, renvoi inclus****Caractéristiques**

- Max : 4,5 l/min (1.2 gpm) - 60 psi**
- Renvoi à bouton poussoir avec trop-plein inclus
- Compatible avec Capteur sans contact ELE-2001-01-xx

Options d'économie d'eau :

- B66-1005-1PL-xx-050 : 0.5 gpm / 1,9 L/min
- B66-1005-1PL-xx-100 : 1.0 gpm / 3,7 L/min

Finis disponibles

- CC : Chrome
- KK : Noir mat
- LL : Laiton satiné
- MM : Or ambré
- BB : Blanc
- NN : Nickel brossé
- YY : Nickel poli
- VV : Cuivre satiné
- TT : Bronze vénitien
- GG : Or

FR

Single-hole lavatory faucet, drain included**Features**

- Max: 1.2 gpm (4,5 l/min) - 60 psi**
- Push-button drain with overflow included
- Compatible with Touchless Sensor ELE-2001-01-xx

Water saving options:

- B66-1005-1PL-xx-050 : 0.5 gpm / 1,9 L/min
- B66-1005-1PL-xx-100 : 1.0 gpm / 3,7 L/min

Available finishes

- CC: Chrome
- KK: Matte black
- LL: Satin brass
- MM: Warm gold
- BB: White
- NN: Brushed nickel
- YY: Polished nickel
- VV: Satin copper
- TT: Venitian bronze
- GG: Gold

EN

