

**Certifications Standards**

ASME A112.18.1 / CSA B125.1 &amp; NSF / ANSI 61

**Robinet de lavabo 8" c/c, renvoi inclus****Caractéristiques**

- Max : 4,5 l/min (1.2 gpm) - 60 psi\*\* †
- Aérateur orientable
- Renvoi à bouton poussoir avec trop-plein inclus
- Compatible avec Capteur sans contact ELE-2001-01-xx

**Options d'économie d'eau :**

- B66-8029-00L-xx-050 : 0.5 gpm / 1,9 L/min†  
 B66-8029-00L-xx-100 : 1.0 gpm / 3,7 L/min

**Finis disponibles**

- CC : Chrome  
 KK : Noir mat  
 LL : Laiton satiné  
 MM : Or ambré  
 BB : Blanc  
 NN : Nickel brossé  
 YY : Nickel poli  
 VV : Cuivre satiné  
 TT : Bronze vénitien  
 KM : Noir titane  
 GG : Or

FR

**8" c/c lavatory faucet, drain included****Features**

- Max: 1.2 gpm (4,5 l/min) - 60 psi\*\* †
- Adjustable aerator
- Push-button drain with overflow included
- Compatible with Touchless Sensor ELE-2001-01-xx

**Water saving options:**

- B66-8029-00L-xx-050 : 0.5 gpm / 1,9 L/min†  
 B66-8029-00L-xx-100 : 1.0 gpm / 3,7 L/min

**Available finishes**

- CC: Chrome  
 KK: Matte black  
 LL: Satin brass  
 MM: Warm gold  
 BB: White  
 NN: Brushed nickel  
 YY: Polished nickel  
 VV: Satin copper  
 TT: Venitian bronze  
 KM: Black titanium  
 GG: Gold

EN

