

**Certifications Standards**

ASME A112.18.1 / CSA B125.1 & NSF / ANSI 61

CMR248 Approval

**Robinet de cuisine monotrou avec douchette rétractable 2 jets****Caractéristiques**

- Max : 6,8 l/min (1.8 gpm) - 60 psi* †
- Douchette 2 jets en laiton à ancrage automatique
- Boyau à connexion « super swivel »
- Bec pivotant permettant à l'utilisateur d'atteindre toutes les zones de l'évier
- Compatible avec Capteur sans contact ELE-1001-01-xx

Options d'économie d'eau :

CUI-9245-02L-xx-150 : 1.5 gpm / 5,7 L/min

Finis disponibles

- CC : Chrome
- SS : Acier inoxydable
- KK : Noir mat
- LL : Laiton satiné
- BB : Blanc
- YY : Nickel poli
- VV : Cuivre satiné
- TT : Bronze vénitien
- GG : Or
- CF : Chrome fumé

FR

Single-hole kitchen faucet with 2-function pull-down spray**Features**

- Max: 1.8 gpm (6,8 l/min) - 60 psi* †
- 2-function brass spray with automatic docking
- Super Swivel hose connection
- Swivel spout allowing to reach all areas of the sink
- Compatible with Touchless Sensor ELE-1001-01-xx

Water saving options:

CUI-9245-02L-xx-150 : 1.5 gpm / 5,7 L/min

Available finishes

- CC: Chrome
- SS: Stainless steel
- KK: Matte black
- LL: Satin brass
- BB: White
- YY: Polished nickel
- VV: Satin copper
- TT: Venitian bronze
- GG: Gold
- CF: Smokey chrome

EN

