



Certifications Standards

ASME A112.18.1 / CSA B125.1



Douchette 1 jet sur raccord mural

Caractéristiques

- Douchette :
- Max : 6,6 l/min (1.75 gpm) - 80 psi*
- Jet simple
- Jets faciles à nettoyer
- Coude de raccordement mural :
- Connexion 1/2" F
- Coude en laiton
- Boyau :
- Écrou conique 1/2" femelle
- Boyau flexible de 59" (150 cm) double agrafe, écrou tournant avec 2 clapets anti-retour
- Boyau en PVC fini KK ou en laiton pour les autres finis

Options d'économie d'eau :

DSP-2561-19-xx-150 : 1.5 gpm / 5,7 L/min

Finis disponibles

CC : Chrome
 KK : Noir mat

FR

1-spray hand shower on wall-mounted supply elbow

Features

- Hand shower:
- Max : 1.75 gpm (6,6 l/min) - 80 psi*
- Single spray pattern
- Easy-to-clean nozzles
- Wall-mounted supply elbow:
- 1/2" F connection
- Brass elbow
- Hose:
- Conical nut 1/2" female
- 59" (150 cm) double interlock flexible hose, rotating nut with 2 non-return valves
- PVC hose in KK finish or brass for other finishes

Water saving options:

DSP-2561-19-xx-150 : 1.5 gpm / 5,7 L/min

Available finishes

CC: Chrome
 KK: Matte black

EN

