



### Certifications Standards

ASME A112.18.1 / CSA B125.1



C

### Finition seule pour valve thermostatique 3/4"

#### Caractéristiques

- 60 l/min (16 gpm) - 60 psi
- Nécessite des valves d'arrêt ou un dérivateur séparés
- Peut facilement fournir 3 accessoires lorsque jumelé au brut RVA-3453-00-B
- Plaque mince de laiton
- Commandez le Brut de valve séparément
- Brut de valve : RVA-3404-00-B

#### Finis disponibles

- CC : Chrome
- KK : Noir mat
- LL : Laiton satiné
- MM : Or ambré
- BB : Blanc
- NN : Nickel brossé
- YY : Nickel poli
- VV : Cuivre satiné
- TT : Bronze vénitien
- GG : Or

FR

### Trim only for 3/4" thermostatic valve

#### Features

- 16 gpm (60 l/min) - 60 psi
- Separate volume control or diverter valve required
- Can easily supply 3 accessories when combined with RVA-9404-00-B
- Thin brass plate
- Order the Rough-in valve separately
- Rough-in valve: RVA-3404-00-B

#### Available finishes

- CC: Chrome
- KK: Matte black
- LL: Satin brass
- MM: Warm gold
- BB: White
- NN: Brushed nickel
- YY: Polished nickel
- VV: Satin copper
- TT: Venitian bronze
- GG: Gold

EN

