



Certifications Standards

ASME A112.18.1 / CSA B125.1

CEC



Finition seule pour robinet de bain mural avec douchette

Caractéristiques

- Bec de bain : 51,5 l/min (13.6 gpm) - 60 psi
- Bec « slip-on » pour ajustement final simplifié
- Douchette : max : 6,6 l/min (1.75 gpm) - 80 psi
- Douchette en laiton ne conduisant pas la chaleur
- Boyau en PVC fini KK ou en laiton pour les autres finis
- Cartouche incluse avec la finition
- Brut : ROU-2003-99-B

Finis disponibles

- CC : Chrome
- KK : Noir mat
- LL : Laiton satiné
- MM : Or ambré
- BB : Blanc
- NN : Nickel brossé
- YY : Nickel poli
- VV : Cuivre satiné
- TT : Bronze vénitien
- GG : Or

FR

Trim only for wall-mounted tub faucet with hand shower

Features

- Bath spout: 13.6 gpm (51.5 l/min) - 60 psi
- Slip-on spout for easier adjustment
- Hand shower: max: 1.75 gpm (6.6 l/min) - 80 psi
- Non-conductive brass hand shower
- PVC hose in KK finish or brass for other finishes
- Cartridge included with the trim
- Rough-in: ROU-2003-99-B

Available finishes

- CC: Chrome
- KK: Matte black
- LL: Satin brass
- MM: Warm gold
- BB: White
- NN: Brushed nickel
- YY: Polished nickel
- VV: Satin copper
- TT: Venitian bronze
- GG: Gold

EN

