

**Certifications Standards**

ASME A112.18.1 / CSA B125.1



C

Finition seule pour valve thermostatique 3/4"**Caractéristiques**

- 60 l/min (16 gpm) - 60 psi
- Nécessite des valves d'arrêt ou un dérivateur séparés
- Peut facilement fournir 3 accessoires lorsque jumelé au brut RVA-3453-00-B
- Plaque mince de laiton
- Commandez le brut de valve séparément
- Brut de valve : RVA-3404-00-B

Finis disponibles

CC : Chrome
 KK : Noir mat
 LL : Laiton satiné
 MM : Or ambré
 BB : Blanc
 NN : Nickel brossé
 YY : Nickel poli
 VV : Cuivre satiné
 TT : Bronze vénitien
 GG : Or

FR

Trim only for 3/4" thermostatic valve**Features**

- 16 gpm (60 l/min) - 60 psi
- Separate volume control or diverter valve required
- Can easily supply 3 accessories when combined with RVA-9404-00-B
- Thin brass plate
- Order the rough-in valve separately
- Rough-in valve: RVA-3404-00-B

Available finishes

CC: Chrome
 KK: Matte black
 LL: Satin brass
 MM: Warm gold
 BB: White
 NN: Brushed nickel
 YY: Polished nickel
 VV: Satin copper
 TT: Venitian bronze
 GG: Gold

EN

