

**Certifications Standards**

ASME A112.18.1 / CSA B125.1



C

Finition seule pour robinet de bain au sol avec douchette**Caractéristiques**

- Bec de bain : 30,4 l/min (8 gpm) - 60 psi
- Inverseur de type bouton poussoir intégré au bec de bain
- Douchette : max : 6,6 l/min (1.75 gpm) - 80 psi
- Douchette en laiton ne conduisant pas la chaleur
- Support de douchette inclinable
- Boyau flexible 150 cm (59") double agrafe, écrou tournant avec 2 clapets anti-retour
- Commandez UN des bruts suivants pour compléter la finition :
- ROU-110C-00-B
- ROU-110W-00-B

Finis disponibles

- CC : Chrome
- KK : Noir mat
- LL : Laiton satiné
- MM : Or ambré
- BB : Blanc
- NN : Nickel brossé
- YY : Nickel poli
- VV : Cuivre satiné
- TT : Bronze vénitien
- GG : Or

FR

Trim only for floor-mounted tub filler with hand shower**Features**

- Bath spout: 8 gpm (30.4 l/min) - 60 psi
- Tub spout with integrated push-button diverter
- Hand shower: max: 1.75 gpm (6.6 l/min) - 80 psi
- Non-conductive brass hand shower
- Reclining hand shower holder
- 59" (150 cm) double interlock flexible hose, rotating nut with 2 non-return valves
- Order ONE of the following rough-in to complete the trim:
- ROU-110C-00-B
- ROU-110W-00-B

Available finishes

- CC: Chrome
- KK: Matte black
- LL: Satin brass
- MM: Warm gold
- BB: White
- NN: Brushed nickel
- YY: Polished nickel
- VV: Satin copper
- TT: Venitian bronze
- GG: Gold

EN

