Fiche Technique / Spec Sheet

T71-9404-00-xx

EVA B71

BARIL



Finition seule pour valve thermostatique 3/4”

Caractéristiques

- 60 l/min (16 gpm) - 60 psi
- Nécessite des valves d’arrêt ou un dérivateur séparés
- Peut facilement fournir 3 accessoires lorsque jumelé au brut RVA-3453-00-B
- Commandez le brut de valve séparément
- Brut de valve : RVA-3404-00-B

Finis disponibles

CC : Chrome
KK : Noir mat
LL : Laiton satiné
MM : Or ambré
BB : Blanc
NN : Nickel brossé
YY : Nickel poli
VV : Cuivre satiné
TT : Bronze vénitien
GG : Or

FR

Certifications ***Standards***

ASME A112.18.1 / CSA B125.1

ADA

UPC

Trim only for 3/4” thermostatic valve

Features

- *16 gpm (60 l/min) - 60 psi*
- *Separate volume control or diverter valve required*
- *Can easily supply 3 accessories when combined with RVA-9404-00-B*
- *Order the rough-in valve separately*
- *Rough-in valve: RVA-3404-00-B*

Available finishes

CC: Chrome
KK: Matte black
LL: Satin brass
MM: Warm gold
BB: White
NN: Brushed nickel
YY: Polished nickel
VV: Satin copper
TT: Venitian bronze
GG: Gold

EN



