

**Certifications Standards**

ASME A112.18.1 / CSA B125.1

**Finition seule pour dérivateur 2 ou 3 voies avec arrêt ou pour valve d'arrêt 3/4"****Caractéristiques**

- Cartouche ultra-longue pour ajustement maximal pouvant être coupée à la longueur requise incluse dans le brut de valve
- Commandez l'UN des bruts de valve séparément
- Bruts de valve : RVA-9562-00-B, RVA-9563-00-B ou RVA-2719-34-B
- Bruts de valve avec position non-partagée (NS) : RVA-9562-00-NS-B, RVA-9563-00-NS-B

Finis disponibles

CB : Chrome blanc
 KB : Noir mat blanc
 LB : Laiton satiné blanc
 MB : Or ambré blanc
 NB : Nickel brossé blanc
 YB : Nickel poli blanc
 VB : Cuivre satiné blanc
 TB : Bronze vénitien blanc
 GB : Or blanc
 BB : Blanc

FR

Trim only for 2 or 3-port diverter with stop or 3/4" stop valve**Features**

- Extra long cartridge for maximum adjustment, that can be cut to required length, included in the rough-in valve
- Order ONE of the rough-in valves separately
- Rough-in valves: RVA-9562-00-B, RVA-9563-00-B ou RVA-2719-34-B
- Rough-in valves with non-shared position (NS) : RVA-9562-00-NS-B, RVA-9563-00-NS-B

Available finishes

CB: Chrome white
 KB: Matte black white
 LB: Satin brass white
 MB: Warm gold white
 NB: Brushed nickel white
 YB: Polished nickel white
 VB: Satin copper white
 TB: Venitian bronze white
 GB: Gold white
 BB: White

EN

