


INEOLINK slim



H920110000001

INEOLINK slim concealed cistern for wall-hung WC and shower WC



This fixture complies with **ASME A112.6.2/A112.19.2/CSA B45.1** as a high-efficiency toilet with a consumption of 0.87 gallons per flush (3.3 lpf).



OVERVIEW

Installation element slim with cistern for wall-hung WC and shower WC. Powder coated, height adjustable steel frame with adjustable feet plates. Installation in studded walls and in front of a solid wall.

Regular installation height 45.2 Inch, installation depth 3.54 ... 5.51 Inch.

Cistern for front operation, with 2-quantity flush system, compatible with intended LAUFEN actuator plates (not included)

Water inlet from the top R ½", silent fill valve.

SPECIFICATION

Certified to	ASME A112.6.2/A112.19.2/CSA B45.1
Design	Self-supporting steel frame for covering with plasterboard, installation onto a wood construction 6" x 2" and 4" x 2", a solid wall or in drywall constructions Powder-coated Feet-adjustable 0 ... 7.87 inch, non-slip leg supports, rotatable foot plates Support for WC ceramic with small contact surfaces Shower toilet ready Front operated Water condensation insulation Dual-flush mechanism LAUFEN EasyFit compatible

Matching for	Wall-hung toilets and shower toilets All INEO flush plates Wood frame construction, INEOGRID railsystem and U-profiles UW 50, UW 75
Scope of delivery	Angle valve ½" Revision box with concealed box and conduit pipe for connection of electronic flush plates Protection box for service opening Fastening material and 2x M12 threaded rods WC connection set DN 90, HDPE Drain elbow DN 90, HDPE with adapter DN 90/110, HDPE
Accessories excl.	Flushing actuator Water inlet adapter NPT ½" Adapter for copper pipe Outlet pipe adapter clamp Ø90mm

TECHNICAL DATA

Cistern	3 ½", material PP Dual-Flushing cable mechanism system Silent fill valve with < 20 dB
Water Connection	Top, R ½", brass
Waste Outlet	DN 90/110, pipe clamp with depth adjustable
Water pressure	0.5 ... 10 bar
Water temperature	max. 25 °C
Installation depth	3 ½" ... 5 ½"
Flushing volume	1.28/0.8 gpf (full/reduced)
Installation height	45.2 Inch, adjustable
Material	Steel, powder coated
Weight	33 lbs
Load capacity	max. 400 kg
Colour	green

DIMENSIONS

